

C-4 Trans

Transmission Oils SAE 30

C-4 Trans SAE 30 is a premium quality Heavy Duty Automatic Transmission Fluid formulated to meet the Allison C-4 specification of Allison Transmission Division of General Motors, U.S.A. The oil is formulated with highly refined base stocks and performance additives to provide superior thermo oxidative stability, clutch friction compatibility, fluoroelastomer seal compatibility, enhanced protection against copper corrosion, reduced foaming.

Specifications :

Meets requirements of:

- * Allison C4 Specifications of Allison Transmission Division of General Motors, USA
- * Caterpillar TO-2
- * Denison HF 0
- * Dexron IID specification of General Motors

Pack Sizes : 20, 55, 210 Ltr

Recommendations :

Bharat Earth Movers Bangalore

- Allison Transmission Division of General Motors, USA
- PALL for use with 6 micron filters
- All Kind of Earthmoving equipments

Main Benefits :

- Excellent filterability
- Provide extended drain interval combined with greater durability of transmission components due to superior thermo-oxidative stability.
- Have the desired friction characteristics for smooth engagement/disengagement of clutch to provide a "soft shift feel".
- Gives outstanding protection against rust and corrosion.



PRODUCT DATA SHEET

Property	Typical Value
SAE Viscosity Grade	30
TBN, mg KOH/g ()ASTM D-2896	11.5
Kinematic Viscosity @40*C, cSt	92
Kinematic Viscosity @100*C, cSt	11
Viscosity Index min.	101
Flash Point, (COC)*C min.	248
Pour Point C Max	-30