

PRIMO ZX

20W50 SL/CF

Primo ZX 20W50 SL/CF oils are high performance engine oils for new generation petrol and diesel vehicles. These oils are blended from high viscosity index base stocks and contain additives to meet the stated performance standards.

Specifications :

API SL in Gasoline & CF in diesel service, US Military MIL-L-6152 B, E-PL 2/ E-DL2 of IS: 13656 - 2002

Recommendations :

Primo ZX 20W50 SL/CF may be recommended for all kind of high-speed, New Generation Petrol & Diesel cars, MUVs & SUVs.

Main Benefits :

- Superior performance in terms of oxidation stability, dispersancy
- Characteristics and energy efficiency.
- Excellent sludge control and extra wear protection at high
- Temperatures and severe operating conditions.
- Outstanding overall engine cleanliness and also provide long engine life.
- Fuel savings and low oil top up.
- Catalytic Converter Compatible.



Pack Sizes :

0.5, 1, 3, 3.5, 4,
5, 55, 210 Ltr

PRODUCT DATA SHEET

Property	Typical Value
TBM, mg KOH / g min.	9.5
Sulphated Ash, % Wt.	0.885
Kinematic Viscosity @40°C, cSt	160.9
Kinematic Viscosity @100°C, cSt	18.3
Viscosity Index min.	130
Flash Point, (COC)*C min.	238
Pour Point C Max	-24