

## PRIMOSYNTH

### 5W30 SM/CF

Primosynth 5W30 SM/CF oils are Semi-synthetic, high performance engine oils for new generation petrol and diesel vehicles. These oils are blended from high viscosity index base stocks and contain additives to meet the stated performance standards.

#### Specifications :

API SM in Gasoline & CF in diesel service, US Military MIL-L-6152 B, E-PL 2/ E-DL2 of IS: 13656 - 2002

#### Recommendations :

Primosynth 5W30 SM/CF may be recommended for all kind of high-speed, New Generation Petrol & Diesel cars, MUVs & SUVs.

#### Main Benefits :

- Superior performance in terms of oxidation stability, dispersancy
- Characteristics and energy efficiency.
- Excellent sludge control and extra wear protection at high
- Temperatures and severe operating conditions.
- Outstanding overall engine cleanliness and also provide long engine life.
- Fuel savings and low oil top up.
- Catalytic Converter Compatible.



#### Pack Sizes :

0.5, 1, 3, 3.5, 4,  
5, 55, 210 Ltr

### PRODUCT DATA SHEET

| Property                        | Typical Value |
|---------------------------------|---------------|
| TBM, mg KOH / g min.            | 10.5          |
| Sulphated Ash, % Wt.            | 0.89          |
| Kinematic Viscosity @40°C, cSt  | 100.1         |
| Kinematic Viscosity @100°C, cSt | 14.8          |
| Viscosity Index min.            | 153           |
| Flash Point, (COC)*C min.       | 238           |
| Pour Point C Max                | -36           |