

TURBO PLUS

15W40 CH-4

Turbo Plus 15W-40 CH4/SJ is API certified, premium commercial multipurpose diesel engine oil. The oil is designed for the most severe performance requirements of new generation diesel engines for on and off highway operations. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations. It exhibits outstanding control on soot induced thickening and soot induced wear.



Specifications :

Meets API CH4, MB 227.0/1, E1-96, MIL-L-46152B

Pack Sizes :

0.5, 1, 2.5, 3, 3.5, 4,
5, 6, 7.5, 10, 20, 55, 210 Ltr

Recommendations :

Turbo Plus- 15W40 CI-4 Plus may be recommended for all kind of high-speed diesel engines in over-the-road, off-highway, contractor equipment and stationary service. It may be recommended for gasoline engines or gasoline engines without emission controls operating under extreme conditions.

Main Benefits :

- Reduced engine scuffing and bore polishing.
- High engine cleanliness.
- Maximum protection from wear and deposits.
- Improved control of oil consumption.
- Easier cold starting.
- Excellent all weather performance

PRODUCT DATA SHEET

Property	Typical Value
TBM, mg KOH / g min.	9.1
Sulphated Ash, % Wt.	1.4
Kinematic Viscosity @40°C, cSt	110
Kinematic Viscosity @100°C, cSt	14.9
Viscosity Index min.	140
Flash Point, (COC)*C min.	235
Pour Point C Max	-33